

tesapack[®] Strong



BNR 5042, 5044, 57165, 57166, 57167, 57168, 57195, 57395, 57424, 57799, 58165, 58166, 58180, 58182, 58195, 58196, 58211, 58212

Product Features

- Strong PP backing
- Solvent-free adhesive with high UV-resistance
- Good sealing security due to high shear adhesive
- Even, low-noise unwinding
- Suitable for use in all tesa[®] hand dispensers

Product Description

tesapack[®] strong is a carton sealing tape made from UV-resistant plastics. It offers low-noise unwinding and strong adhesion for secure packing.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------|--------------------|---------------------|
| • Total thickness | 45 µm | • Type of adhesive | water-based acrylic |
| • Backing material | BOPP | | |

Properties/Performance Values

- | | | | |
|-----------------------|--------------|--------------------------|---------------|
| • Applicationfield | Office, Home | • Hand tearability | no |
| • Solvent free | yes | • Suitable surfaces | Cardboard |
| • Tear resistance | yes | • Adhesive strength | High adhesion |
| • Low noise unwinding | yes | • Ageing resistance (UV) | yes |
| • Tensile strength | 35 N/cm | | |

tesapack[®] Strong

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=05042>